

# TECHNICAL DATA SHEET

## HOLLOW SOFFIT: White & Colour



- Freefoam manufacture a range of PVC-U Hollow Soffits designed to preserve and protect the underside of any roof edge. Freefoam soffit will minimise the risk of trapped moist air and is a long-term solution for easy maintenance.
- A popular choice because of the attractive panelled effect and installation friendly tongue and groove design.
- The Hollow Soffit range is available with a choice of width and all boards are manufactured in 5 metre lengths.
- Freefoam Hollow Soffit is also available in a wide range of colours.
- Freefoam fascia is manufactured from Polyvinyl Chloride - Unplasticised (PVC-U).

Width	100mm - 300mm	Thickness	10mm	Weight	1.25 to 3.6 Kg/m
-------	---------------	-----------	------	--------	------------------

Standard	Characteristic	Result
EN 13245:2008	Mechanical Resistance	(0,5)
EN 13501-1:2007	Reaction to Fire	D-s3, d2/AHM
EN178	Flexure Strength	≥ 39 MPa
EN178	Elongation	≥ 110 %
EN479	Heat Reversion	100° C, <3%
EN478	Heat Ageing	150°C/30 minutes (no bubbling, cracks, delamination)

### Product Certification

- British Board of Agrément (BBA)  
Visit [www.bbacerts.co.uk](http://www.bbacerts.co.uk) for details of BBA Agrément 99/3585
- Centre Scientifique et Technique du Bâtiment (CSTB)  
Visit [www.cstb.fr](http://www.cstb.fr) for details of Avis Technique 2/16-1766



The Freefoam manufacturing site is audited annually by both BBA and CSTB

### Quality System

The Quality System is certified to ISO9001:2015 by SGS.  
The manufacturing site is audited by SGS each year.

